

RNA49 Series

wählen	Anfrage	Bezeichnung	Hauptabmessungen (mm)				Cr	Kor	Ermüdungsgrenze	Referenzgeschwindigkeit	Geschwindigkeit	Gewicht
			Fw	D	C	r	(N)	(N)	Cu (N)	U/min	U/min	(G)
RNA4900	14	22	13	0.3	9600	9200	1630	23600	15400	16.5		
RNA4901	16	24	13	0.3	10600	10900	1640	23200	15900	17.4		
RNA4902	20	28	13	0.3	12000	13600	2430	20400	10800	21.7		
RNA4903	22	30	13	0.3	12400	14600	2600	18800	9900	22.2		
RNA4904	25	37	17	0.3	23700	25500	4600	15800	8900	52.3		
RNA4905	30	42	17	0.3	26500	31500	5700	13600	7400	61		
RNA49-28	32	45	17	0.3	27500	33500	6100	12700	6900	73.2		
RNA4906	35	47	17	0.3	28500	35500	6400	12000	6400	69.4		
RNA4907	42	55	20	0.6	35500	50000	9400	10100	5600	107		
RNA4908	48	62	22	0.6	48500	67000	11500	8900	5000	140		
RNA4909	52	68	22	0.6	51000	73000	12600	8200	4550	182		
RNA4910	58	72	22	0.6	53000	80000	13800	7500	4100	163		
RNA4911	63	80	25	1	65000	100000	17300	6900	3900	255		
RNA4912	68	85	25	1	68000	108000	18800	6400	3600	275		
RNA4913	72	90	25	1	57500	110500	19000	6100	300	295		
RNA4914	80	100	30	1	69000	11200	19500	6000	3400	312		
RNA4915	85	105	30	1	95000	156000	27500	5400	3200	460		
RNA4916	90	110	30	1	97000	162000	28500	5200	3050	489		
RNA4917	100	120	35	1	101000	174000	30500	4900	2850	516		
RNA4918	105	125	35	1.1	125000	237000	41500	4450	2650	657		
RNA4919	110	130	35	1.1	129000	250000	43500	4250	2500	745		
RNA4920	115	140	40	1.1	116000	260000	36000	4100	2410	719		
RNA4922	125	150	40	1.1	124000	270000	28500	3350	1200	693		
RNA4924	135	165	45	1.1	174000	386000	21500	2920	1760	667		
RNA4928	160	190	50	1.1	200000	460000	35000	2900	2350	700		
RNA49-22	28	39	17	0.3	26000	29500	5300	14600	8000	50.2		
RNA49-32	40	52	20	0.6	34500	47500	8900	10700	6000	89.1		