

S 30 K Series

Abmessungen in mm														Felt				Cover				This product is available in the following versions			
wählen	Anfrage	Bezeichnung	d	E	H	EIN	b	C	H1	I	S	S1	S2	Gewicht	Adapter sleeve	Locating Ring	LEXON Lager	LEXON Lager	LEXON Lager	LEXON Lager	Fixed bearing LEXON Lager	LEXON Lager	Floating bearing LEXON Lager	LEXON Lager	
S3024K	110	320	112	380	110	40	215	150	M 24	36	30	17 kg	23024 K/H 3024	FR 10/180	10 x 8,5 - 195	Dimensions according to DIN 5419	DK 128	For closed-end housing	S 3024K AF	S 3024K BF	S 3024K AL	S 3024K BL	S 3024K BL	S 3024K BL	
S3026K	115	350	125	410	120	45	239	160	M 24	36	30	20 kg	23026 K/H 3026	FR 10/200	FR 10/200	Dimensions according to DIN 5419	DK 133	For closed-end housing	S 3026K AF	S 3026K BF	S 3026K AL	S 3026K BL	S 3026K BL	S 3026K BL	
S3028K	125	350	140	410	120	45	260	170	M 24	36	30	25 kg	23028 K/H 3028	FR 10/210	14 x 11 - 225	Dimensions according to DIN 5419	DK 151	For closed-end housing	S 3028K AF	S 3028K BF	S 3028K AL	S 3028K BL	S 3028K BL	S 3028K BL	
S3030K	135	380	150	460	130	45	278	180	M 24	36	30	29 kg	23030 K/H 3030	FR 10/225	4 x 11 - 240	Dimensions according to DIN 5419	DK 161	For closed-end housing	S 3030K AF	S 3030K BF	S 3030K AL	S 3030K BL	S 3030K BL	S 3030K BL	
S3032K	140	39	150	470	130	50	288	190	M 24	36	30	37 kg	23032 K/H 3032	FR 10/240	14 x 11 - 250	Dimensions according to DIN 5419	DK 166	For closed-end housing	S 3032K AF	S 3032K BF	S 3032K AL	S 3032K BL	S 3032K BL	S 3032K BL	
S3034K	150	450	160	540	160	55	320	205	M 30	48	36	45 kg	23034 K/H 3034	FR 10/260	16 x 12 - 270	Dimensions according to DIN 5419	DK 180	For closed-end housing	S 3034K AF	S 3034K BF	S 3034K AL	S 3034K BL	S 3034K BL	S 3034K BL	
S3036K	160	470	170	550	160	55	340	210	M 30	48	36	65 kg	23036 K/H 3036	FR 10/280	16 x 12 - 285	Dimensions according to DIN 5419	DK 190	For closed-end housing	S 3036K AF	S 3036K BF	S 3036K AL	S 3036K BL	S 3036K BL	S 3036K BL	
S3038K	170	470	170	550	160	55	353	220	M 30	48	36	67 kg	23038 K/H 3038	FR 10/290	16 x 12 - 300	Dimensions according to DIN 5419	DK 200	For closed-end housing	S 3038K AF	S 3038K BF	S 3038K AL	S 3038K BL	S 3038K BL	S 3038K BL	
S3040K	180	515	180	610	170	60	373	235	M 30	48	36	72 kg	23040 K/H 3040	FR 10/310	16 x 12 - 315	Dimensions according to DIN 5419	DK 210	For closed-end housing	S 3040K AF	S 3040K BF	S 3040K AL	S 3040K BL	S 3040K BL	S 3040K BL	
S3044K	200	580	200	690	190	70	408	255	M 36	50	42	98 kg	23044 K/H 3044	FR 10/340	16 x 12 - 350	Dimensions according to DIN 5419	DK 230	For closed-end housing	S 3044K AF	S 3044K BF	S 3044K AL	S 3044K BL	S 3044K BL	S 3044K BL	
S3048K	220	610	210	720	200	75	433	265	M 36	50	42	110 kg	23048 K/H 3048	FR 10/360	16 x 12 - 380	Dimensions according to DIN 5419	DK 250	For closed-end housing	S 3048K AF	S 3048K BF	S 3048K AL	S 3048K BL	S 3048K BL	S 3048K BL	
S3052K	240	680	240	820	220	80	485	285	M 45	70	52	148 kg	23052 K/H 3052	FR 10/400	16 x 12 - 410	Dimensions according to DIN 5419	DK 270	For closed-end housing	S 3052K AF	S 3052K BF	S 3052K AL	S 3052K BL	S 3052K BL	S 3052K BL	
S3056K	260	720	250	860	230	80	505	295	M 45	70	52	165 kg	23056 K/H 3056	FR 10/420	16 x 12 - 445	Dimensions according to DIN 5419	DK 290	For closed-end housing	S 3056K AF	S 3056K BF	S 3056K AL	S 3056K BL	S 3056K BL	S 3056K BL	
S3060K	280	780	280	920	260	90	565	320	M 36	50	42	205 kg	23056 K/H 3060	FR 10/440	16 x 12 - 470	Dimensions according to DIN 5419	DK 310	For closed-end housing	S 3060K AF	S 3060K BF	S 3060K AL	S 3060K BL	S 3060K BL	S 3060K BL	
S3064K	300	800	280	940	260	90	570	320	M 36	50	42	235 kg	23064 K/H 3064	FR 10/460	16 x 12 - 505	Dimensions according to DIN 5419	DK 330	For closed-end housing	S 3064K AF	S 3064K BF	S 3064K AL	S 3064K BL	S 3064K BL	S 3064K BL	
S3068K	320	860	300	1000	280	95	615	340	M 36	50	42	280 kg	23068 K/H 3068	FR 10/490	16 x 12 - 535	Dimensions according to DIN 5419	DK 360	For closed-end housing	S 3068K AF	S 3068K BF	S 3068K AL	S 3068K BL	S 3068K BL	S 3068K BL	
S3072K	340	900	320	1060	280	95	655	345	M 36	50	42	340 kg	23072 K/H 3072	FR 10/510	16 x 12 - 565	Dimensions according to DIN 5419	DK 390	For closed-end housing	S 3072K AF	S 3072K BF	S 3072K AL	S 3072K BL	S 3072K BL	S 3072K BL	
S3076K	360	900	330	1060	280	100	675	380	M 36	50	42	400 kg	23076 K/H 3076	FR 10/530	16 x 12 - 600	Dimensions according to DIN 5419	DK 410	For closed-end housing	S 3076K AF	S 3076K BF	S 3076K AL	S 3076K BL	S 3076K BL	S 3076K BL	
S3080K	380	950	350	1100	325	120	715	400	M 36	50	42	460 kg	23080 K/H 3080	FR 10/550	16 x 12 - 630	Dimensions according to DIN 5419	DK 430	For closed-end housing	S 3080K AF	S 3080K BF	S 3080K AL	S 3080K BL	S 3080K BL	S 3080K BL	
S3084K	400	980	375	1160	340	120	750	430	M 36	50	42	500 kg	23084 K/H 3084	FR 10/570	16 x 12 - 660	Dimensions according to DIN 5419	DK 470	For closed-end housing	S 3084K AF	S 3084K BF	S 3084K AL	S 3084K BL	S 3084K BL	S 3084K BL	
S3088K	410	1020	390	1200	340	125	780	430	M 36	50	42	600 kg	23088 K/H 3088	FR 10/590	16 x 12 - 675	Dimensions according to DIN 5419	DK 490	For closed-end housing	S 3088K AF	S 3088K BF	S 3088K AL	S 3088K BL	S 3088K BL	S 3088K BL	
S3092K	430	1080	400	1260	360	130	805	440	M 48	75	56	500 kg	23092 K/H 3092	FR 10/610	16 x 12 - 710	Dimensions according to DIN 5419	DK 510	For closed-end housing	S 3092K AF	S 3092K BF	S 3092K AL	S 3092K BL	S 3092K BL	S 3092K BL	
S3096K	450	1180	410	1380	380	190	825	440	M 48	75	56	800 kg	23096 K/H 3096	FR 10/630	16 x 12 - 740	Dimensions according to DIN 5419	DK 530	For closed-end housing	S 3096K AF	S 3096K BF	S 3096K AL	S 3096K BL	S 3096K BL	S 3096K BL	