

GE...FW

wählen	Anfrage Bezeichnung		Abmessungen in mm							Einzelheiten					Gewicht	Cr CO _r
			d	D	B	Dichtung	C	bk	r1s min.	r2s min.	da max.	Da min.				
GE8-FW	8	19	11	-	5 mm	13 mm	0,3 mm	0,3 mm	9,3 mm	12,5 mm	0,009 kg	5850 N	14600 N			
GE10-FW	10	22	12	-	7 mm	18 mm	0,3 mm	0,3 mm	13,4 mm	17,5 mm	0,02 kg	11400 N	28500 N			
GE12-FW	12	26	15	-	9 mm	22 mm	0,3 mm	0,3 mm	16 mm	21 mm	0,036 kg	17600 N	44000 N			
GE15-FW	15	30	16	-	10 mm	25 mm	0,3 mm	0,3 mm	19,2 mm	24 mm	0,049 kg	22400 N	56000 N			
GE17-FW	17	35	20	-	12 mm	29 mm	0,3 mm	0,3 mm	21 mm	27,5 mm	0,082 kg	31500 N	78000 N			
GE20-FW	20	42	25	-	16 mm	35,5 mm	0,6 mm	0,6 mm	25,2 mm	33 mm	0,16 kg	51000 N	127000 N			
GE25-FW	25	47	28	-	18 mm	40,7 mm	0,6 mm	0,6 mm	29,5 mm	38 mm	0,2 kg	655000 N	166000 N			
GE30-FW-2RS	30	55	32	2RS	20 mm	47 mm	0,6 mm	1 mm	34,4 mm	44,5 mm	0,28 kg	210000 N	350000 N			
GE35-FW-2RS	35	62	35	2RS	22 mm	53 mm	0,6 mm	1 mm	39,7 mm	51 mm	0,38 kg	277000 N	462000 N			
GE40-FW-2RS	40	68	40	2RS	25 mm	60 mm	0,6 mm	1 mm	44,7 mm	57 mm	0,53 kg	360000 N	600000 N			
GE45-FW-2RS	45	75	43	2RS	28 mm	66 mm	0,6 mm	1 mm	50 mm	63 mm	0,67 kg	442000 N	737000 N			
GE50-FW-2RS	50	90	56	2RS	36 mm	80 mm	0,6 mm	1 mm	57,1 mm	75 mm	1,4 kg	690000 N	1150000 N			
GE60-FW-2RS	60	105	63	2RS	40 mm	92 mm	1 mm	1 mm	67 mm	87 mm	2,1 kg	885000 N	1475000 N			
GE70-FW-2RS	70	120	70	2RS	45 mm	105 mm	1 mm	1 mm	78,2 mm	99 mm	3 kg	1125000 N	1875000 N			
GE80-FW-2RS	80	130	75	2RS	50 mm	115 mm	1 mm	1 mm	87,1 mm	108 mm	3,6 kg	1380000 N	2300000 N			
GE90-FW-2RS	90	150	85	2RS	55 mm	130 mm	1 mm	1 mm	98,3 mm	123 mm	5,3 kg	1717000 N	2862000 N			
GE100-FW-2RS	100	160	85	2RS	55 mm	140 mm	1 mm	1 mm	111,2 mm	134 mm	6 kg	1845000 N	3075000 N			
GE110-FW-2RS	110	180	100	2RS	70 mm	160 mm	1 mm	1 mm	124,8 mm	150 mm	9,8 kg	2685000 N	4475000 N			
GE120-FW-2RS	120	210	115	2RS	70 mm	180 mm	1 mm	1 mm	138,4 mm	173 mm	14,6 kg	3015000 N	5025000 N			
GE140-FW-2RS	140	230	130	2RS	80 mm	200 mm	1 mm	1 mm	151,9 mm	191 mm	18,6 kg	3840000 N	6400000 N			
GE160-FW-2RS	160	260	135	2RS	80 mm	225 mm	1 mm	1,1 mm	180 mm	219 mm	24,9 kg	4320000 N	7200000 N			
GE180-FW-2RS	180	290	155	2RS	100 mm	250 mm	1,1 mm	1,1 mm	196,1 mm	239 mm	33,6 kg	6000000 N	1000000 N			
GE200-FW-2RS	200	320	165	2RS	100 mm	275 mm	1,1 mm	1,1 mm	220 mm	267 mm	44,7 kg	6600000 N	11000000 N			
GE220-FW-2RS	220	340	175	2RS	100 mm	300 mm	1,1 mm	1,1 mm	243,6 mm	295 mm	50,8 kg	7200000 N	12000000 N			
GE240-FW-2RS	240	370	190	2RS	110 mm	325 mm	1,1 mm	1,1 mm	263,6 mm	319 mm	64 kg	8550000 N	14250000 N			
GE260-FW-2RS	260	400	205	2RS	120 mm	350 mm	1,1 mm	1,1 mm	283,6 mm	342 mm	81,8 kg	10050000 N	16750000 N			

GE...FW

GE280-FW-2RS	280	430	210	2RS	120 mm	375 mm	1,1 mm	1,1 mm	310,6 mm	370 mm	96,5 kg	10800000 N	18000000 N
--------------	-----	-----	-----	-----	-----------	--------	--------	-----------	-------------	-----------	------------	---------------	------------