

GE...FO



wählen	Anfrage Bezeichnung		Abmessungen in mm						Einzelheiten					Gewicht	Cr CO _r
			d	D	B	Dichtung	C	bk	r1s min.	r2s min.	da max.	Da min.			
GE6-FO	6	16	9	-	5 mm	13 mm	0,3 mm	0,3 mm	9,3 mm	12,5 mm	0,008 kg	5500 N	27500 N		
GE8-FO	8	19	11	-	6 mm	16 mm	0,3 mm	0,3 mm	11,6 mm	15,5 mm	0,014 kg	8150 N	40500 N		
GE10-FO	10	22	12	-	7 mm	18 mm	0,3 mm	0,3 mm	13,4 mm	17,5 mm	0,02 kg	10800 N	54000 N		
GE12-FO	12	26	15	-	9 mm	22 mm	0,3 mm	0,3 mm	16 mm	21 mm	0,034 kg	17000 N	85000 N		
GE15-FO-2RS	15	30	16	2RS	10 mm	25 mm	0,3 mm	0,3 mm	19,2 mm	24 mm	0,046 kg	21200 N	106000 N		
GE17-FO-2RS	17	35	20	2RS	12 mm	29 mm	0,3 mm	0,3 mm	21 mm	27,5 mm	0,077 kg	30000 N	146000 N		
GE20-FO-2RS	20	42	25	2RS	16 mm	35,5 mm	0,3 mm	0,6 mm	25,2 mm	33 mm	0,15 kg	48000 N	240000 N		
GE25-FO-2RS	25	47	28	2RS	18 mm	40,7 mm	0,6 mm	0,6 mm	29,5 mm	38 mm	0,19 kg	62000 N	310000 N		
GE30-FO-2RS	30	55	32	2RS	20 mm	47 mm	0,6 mm	1 mm	34,4 mm	44,5 mm	0,29 kg	80000 N	400000 N		
GE35-FO-2RS	35	62	35	2RS	22 mm	53 mm	0,6 mm	1 mm	39,7 mm	51 mm	0,38 kg	100000 N	500000 N		
GE40-FO-2RS	40	68	40	2RS	25 mm	60 mm	0,6 mm	1 mm	44,7 mm	57 mm	0,54 kg	127000 N	640000 N		
GE45-FO-2RS	45	75	43	2RS	28 mm	66 mm	0,6 mm	1 mm	50 mm	63 mm	0,68 kg	156000 N	780000 N		
GE50-FO-2RS	50	90	56	2RS	36 mm	80 mm	0,6 mm	1 mm	57,1 mm	75 mm	1,4 kg	245000 N	1220000 N		
GE60-FO-2RS	60	105	63	2RS	40 mm	92 mm	1 mm	1 mm	67 mm	87 mm	2 kg	315000 N	1560000 N		
GE70-FO-2RS	70	120	70	2RS	45 mm	105 mm	1 mm	1 mm	78,2 mm	99 mm	2,9 kg	400000 N	2000000 N		
GE80-FO-2RS	80	130	75	2RS	50 mm	115 mm	1 mm	1 mm	87,1 mm	108 mm	3,5 kg	490000 N	2450000 N		
GE90-FO-2RS	90	150	85	2RS	55 mm	130 mm	1 mm	1 mm	98,3 mm	123 mm	5,4 kg	610000 N	3050000 N		
GE100-FO-2RS	100	160	85	2RS	55 mm	140 mm	1 mm	1 mm	111,2 mm	134 mm	5,9 kg	655000 N	3250000 N		
GE110-FO-2RS	110	180	100	2RS	70 mm	160 mm	1 mm	1 mm	124,8 mm	150 mm	9,6 kg	950000 N	4750000 N		
GE120-FO-2RS	120	210	115	2RS	70 mm	180 mm	1 mm	1 mm	138,4 mm	173 mm	15,1 kg	1080000 N	5400000 N		
GE140-FO-2RS	140	230	130	2RS	80 mm	200 mm	1 mm	1 mm	151,9 mm	191 mm	18,8 kg	1370000 N	6800000 N		
GE160-FO-2RS	160	260	135	2RS	80 mm	225 mm	1 mm	1,1 mm	180 mm	219 mm	24,7 kg	1530000 N	7650000 N		
GE180-FO-2RS	180	290	155	2RS	100 mm	250 mm	1,1 mm	1,1 mm	196,1 mm	239 mm	35,4 kg	2120000 N	10600000 N		
GE200-FO-2RS	200	320	165	2RS	100 mm	275 mm	1,1 mm	1,1 mm	220 mm	267 mm	44,8 kg	2320000 N	11600000 N		

GE...FO

GE220-FO-2RS	220	340	175	2RS	100 mm	300 mm	1,1 mm	1,1 mm	243,6 mm	295 mm	50,9 kg	255000 N	12700000 N
GE240-FO-2RS	240	370	190	2RS	110 mm	325 mm	1,1 mm	1,1 mm	263,6 mm	319 mm	64,9 kg	3050000 N	15300000 N
GE260-FO-2RS	260	400	205	2RS	120 mm	350 mm	1,1 mm	1,1 mm	283,6 mm	342 mm	81, 7 kg	3550000 N	18000000 N
GE280-FO-2RS	280	430	210	2RS	120 mm	375 mm	1,1 mm	1,1 mm	310,6 mm	370 mm	96,5 kg	3800000 N	19000000 N